

## Mobil Korea Lube Oil Inc. Ulsan, Korea Date (mm/dd/yyyy): 08/31/2023

## Product: MOBIL SUPER EVERYDAY PROTECTION C2 5W-30

Batch Number	D380603	Туре	1 Lt
Order Key	70489151	Manufacture Date	08/30/2023
Export# / P.O.#		Destination	
Fill #	D380632	Reference #	
Product #	201510203520	T/C or T/T	
Test Description		Method	Test Result
색 (ASTM Color)		ASTM D6045	L3.5
Density @ 15 C, kg/l		ASTM D4052	0.8546
Calcium, mass%		ASTM D4951	0.137
Phosphorus, mass%		ASTM D4951	0.072
저온겉보기점도 (CCS Viscosity) -30 C, mPa.s		ASTM D5293	6001
유동점 (Pour Point), C		ASTM D7346	-42
Infrared Spectrum		MLP13	MATCH
냄새 (Odor)		AMS 1695	PASS
Magnesium, mass%		ASTM D4951	0.038
외관 (Appearance)		AMS 1738	C & B

This material meets the ExxonMobil sales specification established for this product and has been produced in a facility complying with the requirements of the ISO 9001 certified Global Product Integrity Management System (GPIMS). Test results on this certificate represent the most recent inspections done on this product for the stated characteristics and may be based on tank certification, manufacturing data, periodic testing and / or most recent product restock.

QA Chemist

Tests conducted according to International Standard Test Methods are routinely verified to be in compliance with the latest published versions. Minor changes may be made where they have no material impact on test results and are necessitated by reasons such as safety, environmental standards, and method effectiveness.

