

Mobil Korea Lube Oil Inc. Ulsan, Korea Date (mm/dd/yyyy): 08/08/2023

Product: MOBIL SUPER EVERYDAY PROTECTION C3 5W-30

Batch Number	D380088	Туре	1 Lt
Order Key	70486778	Manufacture Date	08/07/2023
Export# / P.O.#		Destination	
Fill #	D380173	Reference #	
Product #	201510203530	T/C or T/T	
Test Description		Method	Test Result
색 (ASTM Color)		ASTM D6045	L3.0
Density @ 15 C, kg/l		ASTM D4052	0.8558
저온겉보기점도 (CCS Viscosity) -30 C, mPa.s		ASTM D5293	6329
Infrared Spectrum		MLP13	МАТСН
냄새 (Odor)		AMS 1695	PASS
외관 (Appearance)		AMS 1738	С&В
Magnesium, Mass%		ASTM D5185	0.040
Calcium, Mass%		ASTM D5185	0.141
Phosphorus, Mass%		ASTM D5185	0.076

This material meets the ExxonMobil sales specification established for this product and has been produced in a facility complying with the requirements of the ISO 9001 certified Global Product Integrity Management System (GPIMS). Test results on this certificate represent the most recent inspections done on this product for the stated characteristics and may be based on tank certification, manufacturing data, periodic testing and / or most recent product restock.

QA Chemist

Tests conducted according to International Standard Test Methods are routinely verified to be in compliance with the latest published versions. Minor changes may be made where they have no material impact on test results and are necessitated by reasons such as safety, environmental standards, and method effectiveness.