

## Certificate of Analysis



Mobil Korea Lube Oil Inc.

Ulsan, Korea

Date (mm/dd/yyyy): 08/22/2023

**Product: MOBIL SUPER TURBO GDI PROTECTION 5W-30**

Batch Number	D380395	Type	1 Lt
Order Key	70488606	Manufacture Date	08/22/2023
Export# / P.O.#		Destination	
Fill #	D380446	Reference #	
Product #	201510107810	T/C or T/T	

Test Description	Method	Test Result
색 (ASTM Color)	ASTM D6045	3.0
Density @ 15 C, kg/l	ASTM D4052	0.8499
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s	ASTM D445	9.6
Calcium, mass%	ASTM D4951	0.268
Phosphorus, mass%	ASTM D4951	0.089
Zinc, mass%	ASTM D4951	0.102
저온겔보기점도 (CCS Viscosity) -30 C, mPa.s	ASTM D5293	4028
유동점 (Pour Point), C	ASTM D7346	-42
Infrared Spectrum	MLP13	MATCH
냄새 (Odor)	AMS 1695	PASS
외관 (Appearance)	AMS 1738	C & B
Foam, Sequence II, Tendency, no Option A, ml	ASTM D892	10
Foam Seq II, Stability (No Option A), ml	ASTM D892	0

This material meets the ExxonMobil sales specification established for this product and has been produced in a facility complying with the requirements of the ISO 9001 certified Global Product Integrity Management System (GPIMS). Test results on this certificate represent the most recent inspections done on this product for the stated characteristics and may be based on tank certification, manufacturing data, periodic testing and / or most recent product restock.

QA Chemist

Tests conducted according to International Standard Test Methods are routinely verified to be in compliance with the latest published versions. Minor changes may be made where they have no material impact on test results and are necessitated by reasons such as safety, environmental standards, and method effectiveness.

**ULS9113869\_CofA**